

Version		Date	
Prepared By			

PRODUCT SPECIFICATION

Category	LED Retrofit Troffer
Item Number	9213
Stock Code	FXRTF25SW/2x2/8CCT3
Mounting	Recessed
Housing Color	White



ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	25/20/16W	Replacement Wattage (W)	
Tested Wattage (W)	25/20/16W		
Input Voltage (V)	120-277	Surge Protect Level	2.5KV RING WAVE
Voltage Frequency (Hz)	50/60	Dimmable	0-10V dim to off
Input Current (A)	0.21 Max	AUX (12V) Line	No
Power Factor	0.9		
THD	<20		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	3125/2500/2000	CCT (K)	3500/4000/5000
Efficacy (lm/w)	125	Beam Angle (°)	110±10
CRI	80		

GENERAL CHARACTERISTICS


Operating Temperature (°F)	-4°F~122°F(-20°C~50°C)
Storage Temperature (°F)	-40°F~185°F(-40°C~85°C)
IP Rating	IP20
Rated Life	L70 > 50000h
Warranty	5 years

ACCESSORIES

Item #	Stock Code	Description

PRODUCT DIMENSIONS

Width- in (mm)	23.90	607.06
Height- in (mm)	3.10	78.74
Length- in (mm)	23.80	604.52
EPA (ft ²)	-	
Weight (lbs)	8.66	
Mounting Height (ft)	-	
Cable Length (ft)	-	



CERTIFICATIONS

UL/ETL	ETL, cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	
DLC	V5.1	RoHs	

DOCUMENTS

LM79		IES File	
LM80		Dimmer List	

COMMENTS

--