

	Produc	t Spec	
Category	Sport Lights		
Item Code	9401	PICTURE	
Stock Code	LED-FX16SPL650/55/840/BK/480		
Mounting	Yoke Mount		
Housing Color	Black		

Housing Color	Black			
Electric (	Characteristics	Photometric	Characteristics	
Rated Wattage (W)	650	Lumen (lm)	93850	
Tested Wattage (W)	651.57	Efficacy (lm/w)	144	
Input Voltage (V)	277~480	CRI	80	
Voltage Frequency (Hz)	50/60	сст (к)	4000	
Input Current (A)		Beam Angle (∘)	NEMA 5x5	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)		Operating Temperature	-40°F~158°F	
Surge protect level	12KV	Storage Temperature	-40°F~158°F	
Dimmable	1-10V	IP rating	IP66	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	10 years	
Produc	t Dimensions	Suggested	l Accessory	
Weight (lbs.)	68		for remote mount	
Height (in)	20.75	20KV surge protector (Included w/ fixture)		
8 ( )		Visor		
Length (in)	14.13	Vi	isor	
Length (in) Width (in)	14.13 17.48	Vi	isor	
Width (in)	17.48	Vi	isor	
		Vi	isor	
Width (in) Mounting Height (ft)	17.48 25~50	Vi	isor	
Width (in) Mounting Height (ft)	17.48 25~50 10	ifications	isor	
Width (in)  Mounting Height (ft)  Cable Length (ft)	17.48 25~50 10		isor √	
Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL	17.48 25~50 10 Qual	ifications		
Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL  Energy Star	17.48 25~50 10 Qual	ifications  LM79	V	
Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL  Energy Star  DLC	17.48 25~50 10 Qual	ifications  LM79  LM80	√ √	
Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL  Energy Star  DLC  CEC	17.48 25~50 10 Qual	ifications  LM79  LM80  IES File	√ √	
Width (in) Mounting Height (ft)	17.48 25~50 10 Qual	ifications  LM79  LM80  IES File  FDA	√ √	