


Version	2.0	Date	4/9/20
Prepared By	JC		

**PRODUCT SPECIFICATION**

<b>Category</b>	Backlit Panel
<b>Item Number</b>	9460
<b>Stock Code</b>	FXPNL40/2x2/8CCT3
<b>Mounting</b>	Recessed
<b>Housing Color</b>	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	40	Replacement Wattage (W)	90-100
Tested Wattage (W)	40		
Input Voltage (V)	120-277V	Surge Protect Level	2.5KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.37 (@120V)	AUX (12V) Line	-
Power Factor	>0.9		
THD	-		


PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	4,480	CCT (K)	3CCT (35/40/50K)
Efficacy (lm/w)	112	Beam Angle (°)	115°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 104°
Storage Temperature (°F)	-4°F ~ 176°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
7338	BAEM8L-60BC/347-A	8W LED Emergency Driver 120-347V with 12" Conduit

**PRODUCT DIMENSIONS**

Width- in / (mm)	23.70"	603
Height- in / (mm)	23.70"	603
Depth- in / (mm)	1.79"	45.5
IK Rating	-	
Weight (lbs)	4.85	
Mounting Height (ft)	8~20	
Cable Length (ft)	-	



CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

**COMMENTS**

--