

natural^{led}

Product Engineering Spec

Product Spec			
Category	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires	PICTURE	
Order #	7647		
Item #	LED-FXSAL29/50K/WH/5S		
Mounting	SB/SF/EA6/PB		
Housing Color	White		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	29	Lumen (lm)	3190
Tested Wattage (W)	29	Efficacy (lm/w)	110
Input Voltage (V)	100-277	CRI	>70
Voltage Frequency (Hz)	50/60	CCT (K)	5000
Input Current (A)	0.25	Beam Angle (°)	Type 5/Flood
Power Factor	0.9	General Characteristics	
Replacement Wattage (W)	100	Operating Temperature	-4°F~122°F
Surge protect level	2KV	Storage Temperature	-22°F~122°F
Dimmable	1-10 V	IP rating	IP 65
THD	<20%	Rated Life	50000 hrs
		Warranty	5 years

Product Dimensions		Suggested Accesory	
Weight (lbs.)	5.95	Photocell	
Height (in)	2.59	Motion Sensor	
Length (in)	13.38		
Width (in)	8.35		
Mounting Height (ft)			
Cable Length (ft)	1.97		

Qualifications			
UL/ETL	ETL	LM79	√
Energy Star		LM80	√
DLC	V4.2 Premium	IES File	√
CEC		FDA	
JA8		NEMA	
FCC	√	Dimmer List	
RoHS	√		

Comments: