

Version	2.0	Date	1/19/2022
Prepared By	J.C		

**PRODUCT SPECIFICATION**

Category	Flood Light
Item Number	9581
Stock Code	FXFDL30/76/40K/BZ-KNC
Mounting	1/2" Knuckle Mount
Housing Color	Bronze (RAL#8019)



**ELECTRICAL CHARACTERISTICS**

Rated Wattage (W)	30	Replacement Wattage (W)	70-100
Tested Wattage (W)	28.86		
Input Voltage (V)	120 ~277	Surge Protect Level	1.5KV
Voltage Frequency (Hz)	50/60	Dimmable	1-10V
Input Current (A)	0.242	AUX (12V) Line	-
Power Factor	≥ 0.9		
THD	≤ 20%		

**PHOTOMETRIC CHARACTERISTICS**

Lumen (lm)	3873	CCT (K)	4000
Efficacy (lm/w)	134	Beam Angle (°)	NEMA 7Hx6V
CRI	80		

**GENERAL CHARACTERISTICS**


Operating Temperature (°F)	-40 ~ 122
Storage Temperature (°F)	-40 ~ 158
IP Rating	IP65
Rated Life	50000 hrs.
Warranty	5 years

**ACCESSORIES**

Item #	Stock Code	Description

**PRODUCT DIMENSIONS**

Width- in (mm)	7.1	180.6
Height- in (mm)	8.93"	226.8
Depth- in (mm)	1.72"	43.7
EPA (ft <sup>2</sup> )	-	
Weight (lbs)	2.42	
Mounting Height (ft)	-	
Cable Length (ft)	-	



**CERTIFICATIONS**

UL/ETL	cULus	CEC	
NSF/ETL Sanitation		JAB	
Energy Star		FCC	✓
DLC	V5.1 Premium	RoHs	✓

**DOCUMENTS**

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

**COMMENTS**

--